

## 303 All Purpose Scaffold Paint

### PRODUCT DESCRIPTION & USES

**303 All Purpose Scaffold Paint** is a cost effective low sheen anticorrosive pure acrylic paint especially designed for application to all substrates used in the construction of scaffolding including timber, aluminium and galvanised steel. It can be applied direct to the substrate without the need of a primer, and is available to order in quantities as low as 1x10L in any corporate colour required by the scaffolding company at a very cost effective price.

### PRODUCT FEATURES

- Low sheen finish.
- Hard wearing
- Exceptional durability.
- Easy application and wash-up with water.
- Low odour.
- Excellent coverage.
- Direct-to-substrate application.
- Quick drying under normal atmospheric conditions.
- Cures down to 5°C.
- Made in New Zealand for New Zealand conditions.

### TECHNICAL DATA

Gloss Level	12-18% at 60° (low sheen)
Primer	Not required.
Wash Up	Water
Colours	To order as selected by the customer.
Pack Size	10L
Storage Temperature	5°C - 50°C
Shelf Life	Minimum 2 years.
Toxicity	Non hazardous waterborne paint formulated without added lead or mercury.
VOC content	13g/L for White as per EC-07-09 and APAS definition of Volatile Organic Compound. Results may vary slightly for the other colours.
Volume Solids	34% for White
Wet Film Thickness	65-100µ per coat
Dry Film Thickness	23-34µ per coat
Coverage	10-15 m <sup>2</sup> /L depending on surface texture, porosity and method of application.

### SUBSTRATE PREPARATION INSTRUCTIONS

Surfaces must be clean and free from all loose material, dirt and heavy chalk. Scrape off peeling and flaking paint. Sand all surfaces to a dull finish and remove sanding dust.

**New Timber, Aluminium or Galvanised Steel:** No primer required. On timber white and light colours may show some signs of tannin staining over knots. Clean and apply 1-2 coats of **303 All Purpose Scaffold Paint**.

**Previously painted surfaces:** No primer required. Remove or treat any corroded metal. Clean and apply 1-2 coats of **303 All Purpose Scaffold Paint**.

### RECOMMENDED APPLICATION METHODS AND TECHNIQUES

Mix the contents in the can thoroughly before and during use.

Apply in full, even coats.

Thin, if required for ease of application in hot or windy conditions or on very porous substrates, with up to 5% water.

Minimum Surface Temperature: 5°C

Maximum Relative Humidity: 75%

Temperature Range: 5°C - 35°C

Suitable Application Methods: Brush, roller or spray

Thinners: Water

Cleaning Solvent: Water

Max. Volume Thinners: 5%

Date Issued: 12 July 2016; Reason for Issue: New Product; Version: 1.0; Replaces Version: N/A; Page 1 of 2

**NOTE:** The information concerning the use and application of this product is intended for use by professional specifiers and applicators, is given in good faith and is believed to be correct at the date of issue. Protective Paints Ltd reserves the right to alter the product or specification without notice. The user should check the date of issue, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of the performance of this product. However certain guarantees may be implied by law.



## 303 All Purpose Scaffold Paint

Nozzle Orifice:	11–15 Thou
Fan Angle:	30°-50°
Nozzle Pressure:	1800 – 2500psi

### DRYING CHARACTERISTICS

All figures quoted are at 20°C and 65% relative humidity.

Drying will take longer at lower temperatures and/or at higher relative humidity and “blooming” may occur.

Do not paint when temperature of surface is below 5°C, above 35°C or when humidity is very high.

Do not apply when rain or dew is expected within 4 hours.

Touch Dry;	1 hour
Recoat:	4 hours
Full Cure:	7 days

### HEALTH & SAFETY

Water based, non-flammable, non-hazardous. Wash off with clean water when in contact with skin as the product may cause dermatitis. Take normal precautions for handling paint i.e. do not ingest, avoid contact with skin and protect eyes from splashes. Refer MSDS, available on request, for detailed safety instructions.

Date Issued: 12 July 2016; Reason for Issue: New Product; Version: 1.0; Replaces Version: N/A; Page 2 of 2

**NOTE:** The information concerning the use and application of this product is intended for use by professional specifiers and applicators, is given in good faith and is believed to be correct at the date of issue. Protective Paints Ltd reserves the right to alter the product or specification without notice. The user should check the date of issue, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of the performance of this product. However certain guarantees may be implied by law.