

A924 Mouldkill X200

PRODUCT DESCRIPTION AND USES

Mouldkill X200 has been developed to kill mould, fungi, algae and lichen in industrial and residential situations. By using a weaker solution and applying on a regular basis this product will ensure a permanently sterile surface.

PHYSICAL PROPERTIES

Appearance	Clear liquid
Size	1L, 4L
Mixing Ratio	See table below
Volume Solids	NA
Product Density	1.0 kg/litre
Shelf Life	Minimum 2 years
Storage Temperature	5-50°C
Drying Time	N/A
Flash Point	N/A

APPLICATION DATA

Refer to the table below to select the mixing ratio most suited to the intended task.

Apply using a garden spray pack or other suitable applicator to spread the product evenly over contaminated surfaces.

For heavy infestation, such as on concrete or clay tile roofing, allow approximately 30 days for the product to kill all growth. All debris should then be removed by low-pressure water blasting. A further application at a mixing ratio specified under "steriliser" will provide good long-term protection of the surface if it is to remain unpainted.

In all other circumstances follow the mixing ratios below and apply evenly over the contaminated surface that can either be left to work overtime, or the material can be removed by low-pressure water blasting to ensure a clean, bright surface.

Situation	Mouldkill X200	Fresh Water
Concrete & clay tile roofing Note: apply and leave for 30 days, Remove debris with low pressure water blasting	1	2
Heavy duty mould & algae on concrete Walls, parapets etc	1	3
Concrete paths & decks	1	4
Exterior concrete / clay floor tiles	1	4
Previously painted surfaces	1	4
Surface contaminated south facing walls	1	4
Green slime & algae	1	4
Steriliser Note: used to maintain mould, algae and lichen free surfaces	1	5

WARNING: Concentrated material may result in severe burns to skin and eyes. Ingestion will result in nausea, vomiting, diarrhoea, burns to the throat and may be fatal.

Thinners	Clean water
Cleaners	Clean water

HEALTH AND SAFETY / STORAGE

For detailed information refer to the product label or SDS, available on request.

OTHER INFORMATION

This product may be used for a wide variety of surfaces. If the surface you propose to paint is not referred to, contact Protective Paints Technical Department for classification. For further technical information please phone 0800 724 684.

The information concerning the use and application of this product is intended for use by professional specifiers and applicators, is given in good faith and is believed to be correct at the date of issue. Protective Paints Ltd reserves the right to alter the product or specification without notice. The user should check the date of issue, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of the performance of this product. However certain guarantees may be implied by law.

ISSUE: 3.0 / June 2026