

Protective Paints Limited, 14B Arwen Place, East Tamaki, PO Box 204293, Highbrook Postal Centre, Manukau 2161 Ph: (09) 274 5606 Ph: 0800 724 684 Fax: (09) 274 0940 Email: reception@propaints.co.nz Website: www.propaints.co.nz

## A924 Mouldkill X200

Mouldkill X200 has been developed to kill mould, fungi, algae and lichen in industrial and residential situations. By using a weaker solution and applying on a regular basis this product will ensure a permanently sterile surface.

#### DIRECTIONS

Refer to the table to select the mixing ratio most suited to the intended task. Apply using a garden spray pack or other suitable applicator to spread the product evenly over contaminated surfaces. For heavy infestation, such as concrete or clay tile roofing, allow approximately 30 days for the product to kill all debris. All debris should then be removed by low pressure waterblasting. A further coat at a mixing ratio specified under "steriliser" will provide good long-term protection of that surface if it is to remain unpainted.

In all other circumstances follow the mixing ratios and apply evenly over the contaminated surface to provide a surface that can either be left in its present state or the material can be removed by low pressure waterblasting to ensure a clean, bright surface.

Situation	Mouldkill X200	Fresh Water
Concrete & clay tile roofing  Note: Apply and leave for 30 days, remove debris with low pressure water blaster	1	2
Heavy duty mould & algae concrete walls, parapets etc	1	3
Concrete paths & decks	1	4
Exterior concrete/clay floor tiles	1	4
Previously painted surfaces	1	4
Surface contaminated south facing walls	1	4
Green slime & algae	1	4
Steriliser Note: Used to maintain mould & lichen free surfaces	1	5

WARNING: Concentrated material may result in severe burns to skin and eyes. Ingestion will result in nausea, vomiting, diarrhoea, burns to the throat and in some cases coma and death.

Pack size

1L, 4L

Flash point

N/A

### **HEALTH AND SAFETY**

Irritant Avoid contact with skin and eyes. Avoid breathing vapour or sanding dust.

When using this product it is recommended that full overalls, gloves, face mask

and goggles be worn. Store container in a safe place when not in use.

Do not burn container.

**FIRST AID** 

EYES Flush with water for at least 15 minutes and seek medical advice.

SKIN Wash contact areas with soap and water. Remove all contaminated clothing,

and seek medical advice. Do not scrub.

INHALATION Remove patient from further exposure, and keep patient warm and

comfortable.

INGESTION Do not induce vomiting. Rinse mouth with water. Seek medical advice as

soon as possible.

# USE ONLY WITH ADEQUATE VENTILATION KEEP OUT OF REACH OF CHILDREN

### TRANSPORTATION AND DISPOSAL

Not Hazchem regulated.

### OTHER INFORMATION

This product may be used for a wide variety of surfaces. If the surface you propose to paint is not referred to, contact Protective Paints Technical Department for classification.

For further technical information please phone 0800 724 684.

### **RELIABILITY OF INFORMATION**

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Since Protective Paints Ltd has no control over product application, purchasers and users must confirm the suitability of our products under their conditions to meet their own requirements.

ISSUE NUMBER: A924 (V2)
ISSUE DATE: 26 September 2013