



000-441P DURASTRIP FAST STRIPPER

PRODUCT DESCRIPTION & USES

A non-caustic fast acting chemical stripper suitable for removing paint from most substrates.

Ideal for the effective removal of 1K and 2K solvent borne paints, particularly varnishes and alkyd enamels.

Not recommended for the removal of acrylic house paints. For these paints use Strippers containing di-basic esters or NMP as the active ingredient.

PRODUCT FEATURES

- Non-caustic.
- Will not darken or deteriorate timber substrates.
- Easy application.
- Made in New Zealand for New Zealand coating types.

TECHNICAL DATA

Gloss Level	Not applicable.
Primer	Not applicable.
Wash Up	Methylated Spirits or hot water.
Colours	Not applicable.
Pack Size	500mL, 1L, 4L, 20L.
Storage Temperature	5°C - 50°C
Shelf Life	Minimum 2 years.
Toxicity	Active ingredient is Methylene Chloride which is a suspected carcinogen.
VOC content	1100g/L as per EC-07-09 and APAS definition of Volatile Organic Compound.
Volume Solids	Not applicable
Wet Film Thickness	2-3mm
Dry Film Thickness	Not applicable
Coverage	3 - 5m ² /L per application.

SUBSTRATE PREPARATION INSTRUCTIONS

General Surface Preparation:

Not applicable.

RECOMMENDED APPLICATION METHODS AND TECHNIQUES

Wear heavy duty protective gloves and eye protection when using **000-441P DuraStrip Fast Stripper**. Sand the paint surface to enhance the effectiveness of **000-441P DuraStrip Fast Stripper**. Paint on to surface freely with an old or disposable natural bristle paintbrush, or use a dip tank. Leave for 1 and 15 minutes to allow the film to soften & blister before removing the softened paint with a scraper. When the bulk of the stripped paint is removed, scrub surface with a plastic scouring pad soaked in methylated spirits. Wash the surface with several applications of methylated spirits to remove all traces of stripper residue and allow to dry thoroughly before sanding and re-coating.

Repeated applications of **000-441P DuraStrip Fast Stripper** may be needed to remove multiple layers of paint or for chemical resistant 2K coatings.

NOTE: Care should be taken when dipping timber furniture as the stripper can weaken glued joints. Fiberglass or plastic substrates may be damaged by the stripper. If paint is to be stripped from these substrates, test strip a hidden part of the item to ensure no permanent damage occurs.

Avoid contact with plastics, Perspex, rubber, linoleum and PVC.

Caution: If stripper is left on for too long it will dry out and the surface will re-harden. If this happens reapply stripper and remove stripped paint while the surface is wet.

Do not shake or stir cans before use and take care when opening cans of **000-441P DuraStrip Fast Stripper** as pressure can build up in the can.

Date Issued: 9 January 2013; Reason for Issue: Correct coverage; Version: 1.1; Replaces Version: 1.0; Page 1 of 2

NOTE: The information concerning the use and application of this product is intended for use by professional specifiers and applicators, is given in good faith and is believed to be correct at the date of issue. Protective Paints Ltd reserves the right to alter the product or specification without notice. The user should check the date of issue, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of the performance of this product. However certain guarantees may be implied by law.



000-441P DURASTRIP FAST STRIPPER

Dispose of stripped paint residue carefully. It is best to leave the stripped paint residue on newspaper on an impervious surface in a well ventilated area until it is dry. The dried paint residue can then be safely disposed of through the normal household waste disposal stream.

Minimum Surface Temperature:	Not applicable
Maximum Relative Humidity:	Not applicable
Temperature Range:	0°C - 35°C
Suitable Application Methods:	Brushing or dipping.
Thinners:	Not applicable
Cleaning Solvent:	Methylated Spirits or hot water.
Max. Volume Thinners:	Not applicable.
Conventional Spray:	Not applicable
Airless Spray:	Not applicable

DRYING CHARACTERISTICS

Not applicable.

Remove softened paint before stripper dries out. If stripper is left on for too long it will dry out and the surface will re-harden.

HEALTH & SAFETY

CAUTION! CONTAINS 870g/L METHYLENE CHLORIDE.

KEEP OUT OF REACH OF CHILDREN

WEAR HEAVY DUTY PROTECTIVE GLOVES AND EYE PROTECTION WHEN USING **000-441P DURASTRIP FAST STRIPPER**.

WARNING: This material is harmful if swallowed or inhaled and will cause skin or eye irritation.

PRECAUTIONS: Avoid breathing vapour - use with adequate ventilation. Do not eat, drink, or smoke whilst using. Store in a cool, well ventilated area indoors between 5°C - 20°C. Dispose of empty container safely. Empty cans or cans containing dry material may be recycled. Do not contaminate any water supply.

FIRST AID

If Swallowed: Give water to dilute. Owing to the aspiration hazard, DO NOT CAUSE VOMITING. Get medical attention without delay.

Eye Contact: Treat immediately with water -- hold open and flush for at least 15 minutes. Get medical attention if irritation persists.

Skin Contact: Remove any contaminated clothing and wash skin thoroughly with soap and water. Avoid scrubbing skin.

Inhalation: Leave the hazard area, maintain breathing and get medical attention.

FIRE: Not applicable.

SPILLS: Absorb with sand or earth. Collect and seal in properly labelled drums for disposal according to local waste management authority.

Refer MSDS, available on request, for detailed safety instructions.

Date Issued: 9 January 2013; Reason for Issue: Correct coverage; Version: 1.1; Replaces Version: 1.0; Page 2 of 2

NOTE: The information concerning the use and application of this product is intended for use by professional specifiers and applicators, is given in good faith and is believed to be correct at the date of issue. Protective Paints Ltd reserves the right to alter the product or specification without notice. The user should check the date of issue, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of the performance of this product. However certain guarantees may be implied by law.

Protective Paints Limited, 14 Arwen Place, East Tamaki, P.O. Box 204 293, Highbrook Postal Centre, Manukau 2161
Ph: (09) 274 5606 Ph: 0800 724 684 Fax: (09)274 0940. Email: reception@propaints.co.nz
<http://www.propaints.co.nz/>; <http://www.portugalcork.co.nz/>; <http://www.paintndecor.co.nz/>