

Protective Paints Limited, 14B Arwen Place, East Tamaki, PO Box 204293, Highbrook Postal Centre, Manukau 2161 Ph: (09) 274 5606 Ph: 0800 724 684 Fax: (09) 274 0940 Email: reception@propaints.co.nz Website: www.propaints.co.nz

234-100 \$Value Wall & Ceiling Flat White

PRODUCT DESCRIPTION AND USES

Protective Paints \$Value Wall & Ceiling Flat White is a water thinned vinyl polymer which exhibits excellent adhesion, sealing and hiding properties. \$Value Wall & Ceiling Flat White is designed for use on suitably prepared and previously unpainted Gibralter board.

PHYSICAL PROPERTIES

Colour/Texture Drying Time Recoat Time Off White/Flat Touch Dry: 30 minutes -1 hour in ambient conditions 2 hours at ambient temperatures

APPLICATION DATA

Ensure surface temperature is above 10°C before application. \$Value Wall & Ceiling Flat White may be applied by brush, roller or spray. One coat of \$Value Wall & Ceiling Flat White followed by two coats of the desired acrylic topcoat should be applied for best results.

 Theoretical Spreading Rate
 Approximately 7-9m²/litre

 Thinners
 Thin product sparingly if needed with clean water

 Clean all equipment immediately after use with clean water

SURFACE PREPARATION

Previously Painted Ceilings Clean thoroughly to remove all dirt, stains, loose and flaking paint prior to application.

TRANSPORTATION AND DISPOSAL

Hazchem not regulated.

OTHER INFORMATION

If the surface you propose to paint is not referred to, contact Protective Paints Technical Department for classification.

For further technical information please phone 0800 724 684.

RELIABILITY OF INFORMATION

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Since Protective Paints Ltd has no control over product application, purchasers and users must confirm the suitability of our products under their conditions to meet their own requirements.

ISSUE NUMBER: 234-100 (V3) ISSUE DATE: 29 April 2016