

## 760-000

### Duralon Polyurethane Gloss

---

#### PRODUCT DESCRIPTION AND USES

Urethane alkyd modified. A single pack polyurethane coating used in high quality architectural finish for interior use. Available in satin and gloss the coating has a fast surface dry, and very good through dry properties resulting in very tough films.  
N.B. Not recommended for exterior use.

---

#### PHYSICAL PROPERTIES

Colour/Texture	Clear/Gloss (also available in Clear /Satin)
Volume Solids	45%
Product Density	0.88kg/litre
Drying Time	Touch Dry: 3-4 hours Hard Dry: 16 hours in ambient conditions
Recoat Time	Minimum: 8 hours
Flash point	38°C

N.B: It is necessary to lightly sand coatings to obtain good intercoat adhesion between applications.

---

#### SURFACE PREPARATION

The surface must be sanded thoroughly, and all dust removed. Before re-varnishing previously coated surfaces all wax must be removed and the surface sanded to a matt finish.

---

#### APPLICATION DATA

Brush, roller or conventional spray.

Recommended D.F.T,	40 microns
Recommended W.F.T.	85 microns
Theoretical Spreading Rate	1.0-1.2m <sup>2</sup> /litre @ 40 microns D.F.T
Thinners	Brushing: R4 Spraying: G5 (5-10%)

---

#### HEALTH AND SAFETY

Irritant  
Avoid contact with skin and eyes. Avoid breathing vapour or sanding dust. When using this product it is recommended that full overalls, gloves, face mask and goggles be worn. Store container in a safe place when not in use. Do not burn container.

---

**FIRST AID****EYES**

Flush with water for at least 15 minutes and seek medical advice.

**SKIN**

Wash contact areas with soap and water. Remove all contaminated clothing, and seek medical advice. Do not scrub.

**INHALATION**

Remove patient from further exposure, and keep patient warm and comfortable.

**INGESTION**

Do not induce vomiting. Rinse mouth with water. Seek medical advice as soon as possible.

---

**TRANSPORTATION AND DISPOSAL**

## Class

3

## Hazchem Code

•3YE (3); •3Y

## UN No

1263

## Packing Group No

III

## Fire Extinguishing Media

CO<sup>2</sup>, Foam, Dry Chemical

## Fire Fighting Procedure

Fire fighters should wear self contained breathing apparatus. Fight fire from a protected location as product may explode on heating. The vapours are heavier than air, so may travel along the ground to accumulate in low areas. Fire may flash back along vapour trail, and can also react with oxidising agents.

Spills should be cleaned up immediately by using sand or other non-flammable absorbent materials. Ensure material does not enter waterways.

Dispose of empty containers in accordance with local by laws.

---

**OTHER INFORMATION**

This product may be used for a wide variety of surfaces. If the surface you propose to paint is not referred to, contact Protective Paints Technical Department for classification.

For further technical information please phone 0800 724 684.

**RELIABILITY OF INFORMATION**

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Since Protective Paints Ltd has no control over product application, purchasers and users must confirm the suitability of our products under their conditions to meet their own requirements.

ISSUE NUMBER: 760-000 (V2a)

ISSUE DATE: 09 October 2013

bwjb