

A893

Prime Plus Ultra

A superior Alkyd Primer for Finger Jointed Pinus Radiata Mouldings. Based on premium grade long oil Alkyd.

PRODUCT FEATURES

- High opacity
- Improved tannin holdout
- Excellent adhesion characteristics
- High volume solids primer
- 27 year history of consistency (since 1985)

Colour	Buff, Beige, Shamrock, OTC Grey, Eco Grey, Pink, White
Appearance When Dry	Low Sheen
Storage Temperature	Minimum 5°C Maximum 50°C
Shelf Life (months)	18
Flash point	40°C
Pack size	20L, 200L, 1000L

ESTIMATION

Percentage by Weight	71.5%
Percentage by Volume	50.5%
Theoretical Coverage	12 – 14m ² /litre

APPLICATION

Machine application by spray, roller, brush.

Potlife (@ 25 deg C)	Single pack
Mixing	Stir thoroughly with a broad paddle to ensure product is fully incorporated before use.
Limitations	Fillet timber stocks to ensure optimum flash off of treatment solvent. High solvent levels will retard drying and may affect topcoats.

DRYING CHARACTERISTICS

Sheen Dry Time Bk3	1 hour, 40 minutes 23°C 60% RH
Temperature (deg. C)	20°C
Touch Dry	4 hours
Handle Dry	8 hours
Full Cure	26 hours
Overcoating	Allow an equivalent of 12 hours at 20°C before overcoating. Can be overcoated with acrylic or oil based paints.

HEALTH AND SAFETY

Irritant	Avoid contact with skin and eyes. Avoid breathing vapour or sanding dust. When using this product it is recommended that full overalls, gloves, face mask and goggles be worn. Store container in a safe place when not in use. Do not burn container.
----------	--

FIRST AID**EYES**

Flush with water for at least 15 minutes and seek medical advice.

SKIN

Wash contact areas with soap and water. Remove all contaminated clothing, and seek medical advice. Do not scrub.

INHALATION

Remove patient from further exposure, and keep patient warm and comfortable.

INGESTION

Do not induce vomiting. Rinse mouth with water. Seek medical advice as soon as possible.

USE ONLY WITH ADEQUATE VENTILATION**KEEP OUT OF REACH OF CHILDREN****TRANSPORTATION AND DISPOSAL**

Class

3

Hazchem Code

•3YE; •3Y

UN No

1263

Packing Group No

III

Fire Extinguishing Media

CO², Foam, Dry Chemical

Fire Fighting Procedure

Fire fighters should wear self contained breathing apparatus. Fight fire from a protected location as product may explode on heating. The vapours are heavier than air, so may travel along the ground to accumulate in low areas. Fire may flash back along vapour trail, and can also react with oxidising agents.

Spills should be cleaned up immediately by using sand or other non-flammable absorbent materials. Ensure material does not enter waterways.

Dispose of empty containers in accordance with local by laws.

OTHER INFORMATION

This product may be used for a wide variety of surfaces. If the surface you propose to paint is not referred to, contact Protective Paints Technical Department for classification.

For further technical information please phone 0800 724 684.

RELIABILITY OF INFORMATION

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Since Protective Paints Ltd has no control over product application, purchasers and users must confirm the suitability of our products under their conditions to meet their own requirements.

ISSUE NUMBER: A893 (V2)

ISSUE DATE: 20 September 2013