

Protective Paints Limited, 14B Arwen Place, East Tamaki, PO Box 204293, Highbrook Postal Centre, Manukau 2161 Ph: (09) 274 5606 Ph: 0800 724 684 Fax: (09) 274 0940 Email: reception@propaints.co.nz Website: www.propaints.co.nz

04.21 FB **Fairing Blend**

PRODUCT DESCRIPTION

Fairing Blend is a premixed powder blend designed to be combined with the Transomarine 4.21 Epoxy System to produce a compound suitable for filling, fairing and covering.

PRODUCT USAGE

Mix approximately 3 volumes of 4.21 Fairing Blend with 1 volume of mixed resin, however quantities can be varied to achieve the desired consistency.

Flash point

101°C

HEALTH AND SAFETY

Irritant

Avoid contact with skin and eyes. Avoid breathing vapour or sanding dust. When using this product it is recommended that full overalls, gloves, face mask and goggles be worn. Store container in a safe place when not in use. Do not burn container.

FIRST AID

EYES SKIN

Flush with water for at least 15 minutes and seek medical advice. Wash contact areas with soap and water. Remove all contaminated

clothing, and seek medical advice. Do not scrub.

INHALATION

Remove patient from further exposure, and keep patient warm and

INGESTION

Do not induce vomiting. Rinse mouth with water. Seek medical advice as

soon as possible.

TRANSPORTATION AND DISPOSAL

Class

9

Hazchem Code

27

UN No

3334

Packing Group No Fire Extinguishing Media N/A

CO2, Foam, Dry Chemical

Fire Fighting Procedure

Fire fighters should wear self contained breathing apparatus. Fight fire from a protected location as product may explode on heating. The vapours are heavier than air, so may travel along the ground to accumulate in low areas. Fire may flash back along vapour trail, and can also react with

oxidising agents.

Spills should be cleaned up immediately by using sand or other non-flammable absorbent materials. Ensure material does not enter

waterways.

Dispose of empty containers in accordance with local by laws.

OTHER INFORMATION

This product may be used for a wide variety of surfaces. If the surface you propose to paint is not referred to, contact Protective Paints Technical Department for classification.

For further technical information please phone 0800 724 684.

RELIABILITY OF INFORMATION

All statements and technical information contained herein are based on tests we believe to be reliable but the accuracy thereof is not guaranteed. Since Protective Paints Ltd has no control over product application, purchasers and users must confirm the suitability of our products under their conditions to meet their own requirements.

ISSUE NUMBER: 04.21FB (V2) ISSUE DATE: 09 August 2013