



830.300 TEREbine LIQUID DRIERS

PRODUCT DESCRIPTION & USES

830.300 Terebine Liquid Driers are a blend of liquid drier metal soaps which can be stirred into decorative oil based or alkyd paints to improve their dry time.

PRODUCT FEATURES

- Easy to add.
- Produced in New Zealand for New Zealand manufactured long oil alkyd paints.

TECHNICAL DATA

Gloss Level	Not applicable.
Primer	Not applicable.
Wash Up	White Spirits, Mineral Turpentine or Protective R4 Thinners.
Colours	Not applicable.
Pack Size	500mL.
Storage Temperature	5°C - 50°C.
Shelf Life	Minimum 2 years.
VOC content	770g/L.
Volume Solids	Not applicable.
Wet Film Thickness	Not applicable.
Dry Film Thickness	Not applicable.
Coverage	Not applicable.

SUBSTRATE PREPARATION INSTRUCTIONS

Not applicable.

RECOMMENDED APPLICATION METHODS AND TECHNIQUES

Add **830.300 Terebine Liquid Driers** in 20mL (1 tablespoon) aliquots to 1L of decorative oil based or alkyd paint to improve the drying characteristics of the product. **Do not exceed an addition level of 100mL of 830.300 Terebine Liquid Driers per 1L of paint.** Driers act on paint like drugs in a human body – a little helps markedly, but too much is worse than none at all. Excess driers can lead to rapid surface drying, which causes wrinkling, and/or surface skinning of the paint, which reduces the ability of the paint to properly through dry.

Within reasonable limits the longer an oil based paint takes to hard dry the better. 8 hours is considered reasonable, 24 hours is better. Quick drying oil based paints exhibit poor weathering resistance and exhibit early flaking and cracking as the film quickly becomes brittle on exposure to the UV rays in sunlight.

HEALTH & SAFETY

CAUTION! FLAMMABLE

CONTAINS 1.5g OF LEAD PER LITRE IN THE FORM OF LEAD NAPHTHENATE.

Flash Point: 38°C.

Contains petroleum solvents: keep away from heat and open flame. Close container when not in use.

KEEP OUT OF REACH OF CHILDREN

WARNING: This material may be harmful if swallowed or inhaled and may cause skin or eye irritation.

Date Issued: 25 February 2015; Reason for Issue: New Issue; Version: 1.0; Replaces Version: N/A; Page 1 of 2

NOTE: The information concerning the use and application of this product is intended for use by professional specifiers and applicators, is given in good faith and is believed to be correct at the date of issue. Protective Paints Ltd reserves the right to alter the product or specification without notice. The user should check the date of issue, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of the performance of this product. However certain guarantees may be implied by law.

Protective Paints Limited, 14 Arwen Place, East Tamaki, P.O. Box 204 293, Highbrook Postal Centre, Manukau 2161
Ph: (09) 274 5606 Ph: 0800 724 684 Fax: (09)274 0940. Email: reception@propaints.co.nz
<http://www.propaints.co.nz/>; <http://www.portugalcork.co.nz/>; <http://www.paintndecor.co.nz/>



830.300 TEREbine LIQUID DRIERS

PRECAUTIONS: Avoid breathing vapour - use with adequate ventilation. Do not eat, drink, or smoke whilst using. Store in a cool, well ventilated area indoors between 5°C - 20°C. Dispose of empty container safely. Empty cans or cans containing dry material may be recycled. Do not contaminate any water supply.

FIRST AID

If Swallowed: Give water to dilute. Owing to the aspiration hazard of hydrocarbon solvents, **DO NOT CAUSE VOMITING**. Get medical attention without delay.

Eye Contact: Treat immediately with water -- hold open and flush for at least 15 minutes. Get medical attention if irritation persists.

Skin Contact: Remove any contaminated clothing and wash skin thoroughly with soap and water. Avoid scrubbing skin.

Inhalation: Leave the hazard area, maintain breathing and get medical attention.

FIRE: Use foam, carbon dioxide or dry chemical powder.

SPILLS: Absorb with sand or earth. Collect and seal in properly labelled drums for disposal according to local waste management authority.

Refer MSDS, available on request, for detailed safety instructions.

Date Issued: 25 February 2015; Reason for Issue: New Issue; Version: 1.0; Replaces Version: N/A; Page 2 of 2

NOTE: The information concerning the use and application of this product is intended for use by professional specifiers and applicators, is given in good faith and is believed to be correct at the date of issue. Protective Paints Ltd reserves the right to alter the product or specification without notice. The user should check the date of issue, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of the performance of this product. However certain guarantees may be implied by law.

Protective Paints Limited, 14 Arwen Place, East Tamaki, P.O. Box 204 293, Highbrook Postal Centre, Manukau 2161
Ph: (09) 274 5606 Ph: 0800 724 684 Fax: (09)274 0940. Email: reception@propaints.co.nz
<http://www.propaints.co.nz/>; <http://www.portugalcork.co.nz/>; <http://www.paintndecor.co.nz/>