

830-300 Terebine Liquid Driers

PRODUCT DESCRIPTION AND USES

830-300 Terebine Liquid Driers are a blend of liquid drier metal soaps which can be stirred into decorative oil based or alkyd paints to improve their dry time.

- Easy to add
- Lead free
- Made in New Zealand for New Zealand manufactured long oil alkyd paints

PHYSICAL PROPERTIES

Appearance	Brown liquid
Size	500ml, 1L
Mixing Ratio	Initially 20ml/L up to 100ml/L
Volume Solids	N/A
Product Density	0.81 kg/litre
Shelf Life	Minimum 2 years
Storage Temperature	5-35°C
Flash Point	38°C

APPLICATION DATA

Add 830-300 Terebine Liquid Driers in 20 mL (approximately 1 tablespoon) increments to 1 L of decorative oil-based or alkyd paint to improve drying performance.

Do not exceed 100 mL of 830-300 Terebine Liquid Driers per litre of paint. Driers are most effective when added in small quantities; a small addition can significantly improve drying, while excessive amounts may adversely affect performance. Overdosing can cause rapid surface drying, resulting in wrinkling and/or surface skinning. This may inhibit proper through-drying of the paint film and reduce overall coating performance.

Within reasonable limits the longer an oil-based paint takes to hard dry the better. 8 hours is considered reasonable, 24 hours is better. Quick drying oil-based paints exhibit poor weathering resistance and exhibit early flaking and cracking as the film quickly becomes brittle on exposure to the UV rays in sunlight.

Thinners	Not required
Cleaners	Mineral Turpentine, White Spirits or Protective Paints R4 Thinners

HEALTH AND SAFETY / STORAGE

For detailed information refer to the product label or SDS, available on request.

OTHER INFORMATION

This product may be used for a wide variety of surfaces. If the surface you propose to paint is not referred to, contact Protective Paints Technical Department for classification. For further technical information please phone 0800 724 684.

The information concerning the use and application of this product is intended for use by professional specifiers and applicators, is given in good faith and is believed to be correct at the date of issue. Protective Paints Ltd reserves the right to alter the product or specification without notice. The user should check the date of issue, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of the performance of this product. However certain guarantees may be implied by law.

ISSUE: 2.0 / June 2026