



# 01.000 NON-SKID ADDITIVE

## PRODUCT DESCRIPTION & USES

**01.000 Non-Skid Additive** is a calcite mineral aggregate which is added to or broadcast over Paving Paint that is applied to pedestrian surfaces where it is essential that a slip resistant finish is achieved.

## PRODUCT FEATURES

- Non-hazardous.
- Does not contain crystalline silica.
- Easy application.
- Produced in New Zealand for New Zealand coating types.

## TECHNICAL DATA

Gloss Level	Not applicable.
Primer	Not applicable.
Wash Up	Not applicable.
Colours	Not applicable.
Pack Size	500g, 1kg.
Storage Temperature	Not applicable.
Shelf Life	Indefinite.
Toxicity	Non-hazardous.
VOC content	Nil
Volume Solids	100%
Wet Film Thickness	Not applicable.
Dry Film Thickness	Not applicable
Coverage	20 – 30g/m <sup>2</sup> .

## SUBSTRATE PREPARATION INSTRUCTIONS

Refer TDS of product in which **01.000 Non-Skid Additive** is being used for applicable surface preparation instructions.

## RECOMMENDED APPLICATION METHODS AND TECHNIQUES

Add 200 to 300 grams of **01.000 Non-Skid Additive** per liter of paint to achieve a non-skid finish. Apply two coats of paint at 8 to 10 m<sup>2</sup>/L per coat.

When added to **A112 Alkyd Floor & Paving High Gloss Enamel** 200g/L of **01.000 Non-Skid Additive** will achieve a non-skid surface with a coefficient of resistance of 0.70 dry and 0.66 wet when tested to AS/NZS 3661.1:1993 Slip Resistance of Pedestrian Surfaces.

An alternate method of use is to apply one coat of **A112 Alkyd Floor & Paving High Gloss Enamel** to the floor then, while the paint is still tacky, sprinkle **01.000 Non-Skid Additive** using a sieve or coarse shaker at a rate of 20 to 30 g/m<sup>2</sup>. When dry lightly sweep the surface to remove any non-adhering grit and overcoat with one or two coats of **A112 Alkyd Floor & Paving High Gloss Enamel**.

## HEALTH & SAFETY

Non-hazardous aggregate containing no crystalline silica. Take normal precautions for handling limestone minerals i.e. do not ingest, avoid inhaling dust when pouring into paint or sprinkling over a painted surface.

Refer MSDS, available on request, for detailed safety instructions.

Date Issued: 26 June 2018; Reason for Issue: Update letterhead and website links; Version: 1.1; Replaces Version: 1.0; Page 1 of 1

**NOTE:** The information concerning the use and application of this product is intended for use by professional specifiers and applicators, is given in good faith and is believed to be correct at the date of issue. Protective Paints Ltd reserves the right to alter the product or specification without notice. The user should check the date of issue, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of the performance of this product. However certain guarantees may be implied by law.

Protective Paints Limited, 14 Arwen Place, East Tamaki, P.O. Box 204 293, Highbrook Postal Centre, Manukau 2161  
Ph: (09) 274 5606 Ph: 0800 724 684 Fax: (09)274 0940. Email: [reception@propaints.co.nz](mailto:reception@propaints.co.nz)  
<http://www.protectivepaints.co.nz/>; <http://www.portugal cork.co.nz/>; <http://www.paintanddecor.co.nz/>