



312 Acrylic Glaze Coat

PRODUCT DESCRIPTION & USES

Protective Acrylic Glaze Coat is a water based acrylic glaze designed for exterior surfaces such as masonry. It can be applied direct without the need for a primer, or used as a glaze over other coatings.

Note: This product is not suitable in areas subjected to ponded water or vehicular traffic.

PHYSICAL PROPERTIES

Colour/Texture	Clear / Gloss
Sizes	4L, 10L, 20L
Drying Time	Approximately 30 minutes depending on weather conditions
Recoat Time	2 hours depending on weather conditions

SURFACE PREPARATION

Remove all loose and flaking paint. Any glossy surfaces should be sanded and wiped down. Ensure surface is clean and dry.

APPLICATION DATA

Ensure surface temperature is above 10°C before application. Acrylic Glaze Coat can be applied by brush, roller or spray. Sound preparation practice should be observed for maximum durability. Two coats of Acrylic Glaze Coat should be applied to the surface for best durability and appearance.

Ensure product is stirred and properly mixed prior to use.

Theoretical Spreading Rate	Will vary depending on porosity of substrate and conditions 14m ² /L for smooth or previously painted surfaces 8-10m ² /L for rough surfaces
-----------------------------------	--

Thinners	The product can be thinned using clean water Brushes and equipment should be cleaned immediately after use with clean water
-----------------	--

TRANSPORTATION AND DISPOSAL

Hazchem not regulated.

Date Issued: 18 March 2019; Reason for Issue: new format; Version: 3.0; Replaces Version: 2; Page 1 of 1

NOTE: The information concerning the use and application of this product is intended for use by professional specifiers and applicators, is given in good faith and is believed to be correct at the date of issue. Protective Paints Ltd reserves the right to alter the product or specification without notice. The user should check the date of issue, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of the performance of this product. However certain guarantees may be implied by law.