

999-100 Strippable Coating

PRODUCT DESCRIPTION & USES

999-100 Strippable Coating is a white translucent single pack, spray applied, peelable coating which gives a tough, flexible, impervious dried film that is easily removed.

999-100 Strippable Coating is applied to clean spray booth walls and floors producing a peelable barrier that makes removal of dried over-spray easier during the cleaning of the booth.

999-100 Strippable Coating is used to provide a peelable skin on surfaces where protection from overspray, dirt, and scratches is required. When protection is no longer needed, the removal of **999-100 Strippable Coating** requires no solvents – simply peel off the coating.

TECHNICAL DATA

Gloss Level	Semi Gloss
Primer	Not applicable
Colours	Translucent White
Product Size	4L
Storage Temperature	5°C - 50°C
Shelf Life	Minimum 2 years
VOC content	685g/L as per EC-07-18 definition of Volatile Organic Compound
Volume Solids	19%
Wet Film Thickness	125-175µ
Dry Film Thickness	24-32µ
Coverage	6-8m ² /L

SUBSTRATE PREPARATION INSTRUCTIONS

Surface must be clean of grease, oil and dirt.

RECOMMENDED APPLICATION METHODS AND TECHNIQUES

Mix the contents in the can thoroughly before and during use.

Apply a single heavy wet coat so the coating sags slightly.

Allow to dry for at least 24 hours before re-commissioning the spray booth.

Some cobwebbing may occur with certain types of equipment, but this does not detract from the product performance.

Notes:

1. This product is specially formulated for application to smooth metal surfaces. For non-metallic or coated surfaces please test before use to ensure that **999-100 Strippable Coating** peels off easily after application.
2. Do not apply in several light coats, as this makes removal difficult.
3. Once there is sufficient build up of overspray in the booth, peel **999-100 Strippable Coating** from the surface. Damp peeled overspray and coating with water and dispose of via your normal industrial waste collection.

Minimum Surface Temperature:	5°C
Maximum Relative Humidity:	75%
Temperature Range:	5°C - 35°C
Suitable Application Methods:	Spray, Airless Spray or Air-Assisted Spray
Thinners:	09.04 Spraying Thinner
Cleaning Solvent:	09.04 Spraying Thinner
Max. Volume Thinners	Not usually required
Cleaning Solvent:	Water
Nozzle Orifice:	9-13 Thou
Fan Angle:	30° - 50°
Nozzle Pressure:	1000 – 1500 psi

DRYING CHARACTERISTICS

All figures quoted are at 25°C and 65% relative humidity.

Drying will take longer at lower temperatures and/or at higher relative humidity.

Do not paint when temperature of surface is below 5°C, above 35°C or when humidity is very high.

Do not apply when rain or dew is expected within 4 hours.

Touch Dry:	15-20 minutes
Recoat:	1 hour
Full Cure:	2-3 hours



999-100 Strippable Coating

HEALTH & SAFETY

CAUTION! FLAMMABLE

Flash Point: 40C.

Contains petroleum solvents: keep away from heat and open flame. Close container when not in use.

KEEP OUT OF REACH OF CHILDREN

WARNING: This material may be harmful if swallowed or inhaled and may cause skin or eye irritation.

PRECAUTIONS: Avoid breathing vapour -- use with adequate ventilation. Do not eat, drink, or smoke whilst using. Store in a cool, well ventilated area indoors between 5°C - 20°C. Dispose of empty container safely. Empty cans or cans containing dry material may be recycled. Do not contaminate any water supply.

FIRST AID

If Swallowed: Give water to dilute. Owing to the aspiration hazard of hydrocarbon solvents, DO NOT CAUSE VOMITING. Get medical attention without delay.

Eye Contact: Treat immediately with water -- hold open and flush for at least 15 minutes. Get medical attention if irritation persists.

Skin Contact: Remove any contaminated clothing and wash skin thoroughly with soap and water. Avoid scrubbing skin.

Inhalation: Leave the hazard area, maintain breathing and get medical attention.

FIRE: Use foam, carbon dioxide or dry chemical powder.

SPILLS: Absorb with sand or earth. Collect and seal in properly labelled drums for disposal according to local waste management authority.

Refer MSDS, available on request, for detailed safety instructions.

Date Issued: 26 September 2018; Reason for Issue: New Product; Version: 1.0; Replaces Version: N/A; Page 2 of 2

NOTE: The information concerning the use and application of this product is intended for use by professional specifiers and applicators, is given in good faith and is believed to be correct at the date of issue. Protective Paints Ltd reserves the right to alter the product or specification without notice. The user should check the date of issue, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of the performance of this product. However certain guarantees may be implied by law.

Protective Paints Limited, 14 Arwen Place, East Tamaki, P.O. Box 204 293, Highbrook Postal Centre, Manukau 2161

Ph: (09) 274 5606 Ph: 0800 724 684. Email: orders@propaints.co.nz
<http://www.protectivepaints.co.nz/>; <http://www.portugalcork.co.nz/>