

236 TradeUP All Purpose Primer Undercoat

PRODUCT DESCRIPTION AND USES

TradeUp All Purpose Primer Undercoat is a premium acrylic Primer Sealer suitable for most general surfaces. It provides excellent adhesion and is recommended for use on gib board, plaster, fibrous plaster, coving, fibrolite, timber, brick, block and for priming concrete roof tiles. A broad-spectrum biocide is incorporated into the dry film, ensuring durable resistance against mould and mildew growth in damp conditions.

- Water-based for low odour and easy application
- Built-in fungicidal protection against mould and mildew
- Resists moisture, staining and household cleaning agents
- Simple water clean-up
- Made in New Zealand for New Zealand conditions

PHYSICAL PROPERTIES

| | |
|---------------------|--|
| Appearance | White / Matt |
| Gloss Level | 2-4% at 60° |
| Size | 10L |
| Volume Solids | 37% |
| Product Density | 1.45kg/litre |
| Shelf Life | Minimum 2 years (unopened) |
| Storage Temperature | 5-50°C |
| VOC Content | 50g/L as per EC07-09 and APAS definition of Volatile Organic compounds |
| Drying Time (25°C) | Tack Dry: 30 minutes |
| Recoat Time (25°C) | 2 hours |

SURFACE PREPARATION

Some caution should be taken when painting over plaster stopping containing oil additives (e.g. milk), as adhesion may be impaired. Surfaces to be coated must be clean and dry. Remove all loose or flaking paint, dirt, grease, and other contaminants, and ensure the substrate is thoroughly prepared prior to application.

This primer sealer can be overcoated with a wide range of TradeUp topcoats, including 233 TradeUp Wet Area Low Sheen, 231 TradeUp Wall & Ceiling Satin White, 234 TradeUp Wall & Ceiling Flat White, 235 TradeUp Wall & Ceiling Low Sheen White, 230 TradeUp Exterior Gloss White, 232 TradeUp Exterior Low Sheen, and 237 TradeUp Exterior Semi Gloss White, providing excellent versatility for both interior and exterior applications.

APPLICATION DATA

May be applied by brush, roller or spray.

Sound preparation is essential to obtain maximum durability.

Mix the contents in the can thoroughly before and during use. Apply in full, even coats.

Do not apply if temperature is below 10°C or humidity is above 85%.

Drying will take longer at lower temperatures and/or at higher relative humidity.

Thin product sparingly if needed with clean water. Clean all equipment immediately after use with clean water.

| | |
|----------------------------|---------------------------|
| Recommended D.F.T | 29-37 microns |
| Recommended W.F.T | 80-100 microns |
| Theoretical Spreading Rate | 6-10m ² /litre |
| Thinners / Cleaner | Water |

HEALTH AND SAFETY / STORAGE

For detailed information refer to the product label or SDS, available on request.

OTHER INFORMATION

This product may be used for a wide variety of surfaces. If the surface you propose to paint is not referred to, contact Protective Paints Technical Department for classification. For further technical information please phone 0800 724 684.

The information concerning the use and application of this product is intended for use by professional specifiers and applicators, is given in good faith and is believed to be correct at the date of issue. Protective Paints Ltd reserves the right to alter the product or specification without notice. The user should check the date of issue, and if more than 24 months have elapsed, should verify with our nearest sales office that the information is still current. Because we cannot control the way these products may be used, or the conditions they may be exposed to, we can give no express guarantees in respect of the performance of this product. However certain guarantees may be implied by law.

ISSUE: 1.0 / Sep 2025